



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI 50 - Equipment for Swimming Pools, Spas, Hot Tubs and Other Recreational Water Facilities

This is the Official Listing recorded on December 7, 2023.

Guangdong Liansu Technology Industrial Co., Ltd. DBA Lesso America, Inc.
Liansu Industrial Estate
Longjiang Town, Shunde Zone
Foshan, Guangdong 528318
China
86 757 2388 8337

Facility: # 2 China

Materials and Components

Polyvinyl Chloride (PVC)
LESSO PVC Fittings^{[1] [2] [3]}

[1] Figure numbers may have the following prefix used to identify retail packaging requirements: R. Suffix indicates size and configuration:

(W)(XX) - (YYY)
IR90-(YYY), Compression Coupling (GASKET x GASKET)
IR91-(YYY), Compression Tee (GASKET x GASKET x FIPT)
FSF-(YYY), Expand Repair Coupling (SOC x SPIG)

(W) 4 - Sch 40
8 - Sch 80

(XX) Type of fitting
52 - Floor Flange (FIPT)
97 - Union w/ O-ring Seal (SOC x SOC)
98 - Union w/ O-ring Seal (FIPT x FIPT)

(YYY) - Size of fitting

[2] Material complies with NSF/ANSI Standard 14 potable water requirements. Fittings NSF Listed to NSF/ANSI Standard 14.

[3] Figure numbers may have the following prefix used to identify retail packaging requirements: R

Suffix indicates size and configuration:

(V)(W)(XX) - (YYY)(Z)
(V)(W)(XX) - (YYYY)(Z)

(V) D - Deep Socket (1/2" branch outlet only)
No Prefix - Standard Socket

(W) 4 - Sch 40
8 - Sch 80

(XX) Type of fitting
01 - Tee or Reducing Tee SOC X SOC X SOC
02 - Tee or Reducing Tee SOC X SOC X FIPT
03 - Tee SOC X FIPT X SOC
04 - 90° Street Ell SPIG X FIPT
05 - Tee FIPT X FIPT X FIPT
06 - 90° Ell or 90° Sweep Ell or 90° Reducing Ell SOC X SOC
07 - 90° Ell or 90° Reducing Ell SOC X FIPT
08 - 90° Ell FIPT X FIPT
09 - 90° Street Ell SPIG X SOC
10 - 90° Street Ell or Reducing 90° Street Ell MIPT X SOC
11 - 11-1/4° Ell SOC X SOC
12 - 90° Street Ell MIPT X FIPT
13 - Side Outlet Ell SOC X SOC X SOC
14 - Side Outlet Ell SOC X SOC X FIPT
16 - 22-1/2° Ell SOC X SOC

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



- 17 - 45° Ell SOC X SOC
- 19 - 45° Ell FIPT X FIPT
- 20 - Cross or Reducing Cross SOC X SOC X SOC X SOC
- 27 - 45° Street Ell SPIG X SOC
- 29 - Coupling or Reducing Coupling or Eccentric Reducer Coupling SOC X SOC
- 30 - Coupling or Reducing Coupling FIPT X FIPT
- 34 - Riser Extension FIPT X MIPT
- 35 - Female Adapter or Reducing Female Adapter SOC X FIPT
- 36 - Male Adapter or Reducing Male Adapter MIPT X SOC
- 37 - Reducing Bushing Flush Style SPIG X SOC
- 38 - Reducing Bushing Flush Style SPIG X FIPT
- 39 - Reducing T.T. Bushing Flush Style FIPT X MIPT
- 42 - 22-1/2°Street ELL SPIG x SDC
- 44 - Street Tee SPIG X SOC X SOC
- 47 - Cap SOC
- 48 - Cap FIPT
- 49 - Plug SPIG
- 50 - Plug MIPT
- 61 - Male Adapter (Take off) SPIG X MIPT
- 75 - Wye or Reducing Wye SOC X SOC X SOC
- 78 - Spigot Female Adapter SPIG x FIPT
- 79 - Deep Socket Coupling SOC X SOC

(YYY) or (YYYY) - Size of fitting

- (Z) N - Nesting
- F - Fabricated fitting
- FE - Fabricated/Eccentric fitting
- E - Eccentric fitting
- No Suffix - Standard style
- S - Sweep

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.